

REVISIONS This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR. DESCRIPTION INITIAL APPROVED REV ECR DATE 1.98 − 1.025 —► .50 .513 .48 2X .25 1.588 -2X ∅ .276 THRU ALL 2.37 ===== ===== -4X .10 X 45° M8X1.25 - 6H THRU ALL-



**UPPER SERVO CONTROL AXLE EXCHANGE** 

RBEM632V3023125-3 MAT'L A36/1018/1020 HR TREAT
FINISH POWDER COAT YELLOW SPEC FED #13538 DRAWN BY: DUERFELDT CHECKED: MACKOVJAK OPPS APPR:

1:1

SCALE

DIMENSIONS ARE IN INCHES
.XXX ± .005 FRACTIONS ± 1/8
.XX ± .01 ANGLES ±.5° .XX ± .01 .X ± .1 SURFACES = 125/

1. BREAK ALL SHARP EDGES .015 x 45 'OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009

UNLESS OTHERWISE SPECIFIED

SHEET 3 OF 6

ANDERSON QA APPR: USED ON MODEL LINDSAY APPROVED: GILBERT H175

3/24/2016

THREADED PLATE

REVISIONS This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR. REV ECR DESCRIPTION DATE INITIAL APPROVED **-** 1.025 **-**.50 .48 -2X .25 −2X Ø .276 THRU ALL 1.588 - FULL R 2.37

-6X .10 X 45°



UPPER SERVO CONTROL AXLE EXCHANGE

RBEM632V3023125-5						REV 1
MAT'L A36/1018/1020 HR				UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX ± .005 FRACTIONS ± 1/8 .XX ± .01 ANGLES ± .5° .X ± .1 SURFACES = 125  1. BREAK ALL SHARP EDGES		
HEAT TREAT						
FINISH POWDER COAT YELLOW						
SPEC FED #13538						
DRAWN BY:	DUERFELDT			.015 x 45° OR .015R -2. DIMENSIONAL LIMITS APPLY AFTER PLATING -3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009		
CHECKED:	MACKOVJAK					
OPPS APPR:	ANDERSON					
QA APPR:	LINDSAY			USED ON MODEL		
APPROVED:	GILBERT			H175		
SCALE	1:1 DATE 3		3/2	24/2016	SHEET 4 OF	6



-1.295

**BASE PLATE** 

REVISIONS This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR. DESCRIPTION INITIAL APPROVED REV ECR DATE - 1.98 -**--** 1.025 **--**.48 - .513 2X .25 -2X Ø .257 THRU ALL 1.588 FULL R 2.37 -1.295-6X .10 X 45° UPPER SERVO CONTROL AXLE EXCHANGE RBEM632V3023125-7 MAT'L WHITE DELRIN UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES
.XXX ± .005 FRACTIONS ± 1/8
.XX ± .01 ANGLES ±.5° .XX ± .01 .X ± .1 SURFACES = 125 SPEC 1. BREAK ALL SHARP EDGES .015 x 45 'OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009 DRAWN BY: DUERFELDT CHECKED: MACKOVJAK OPPS APPR: ANDERSON

**BASE PAD** 

QA APPR:

SCALE

APPROVED:

LINDSAY

GILBERT

1:1

USED ON MODEL


H175


SHEET 5 OF 6

3/24/2016

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR. 
 REVISIONS

 REV
 ECR
 DESCRIPTION
 DATE
 INITIAL
 APPROVED





NOTE:

NO POWDER COAT THIS SURFACE.

## DARI

ÜPPER SERVO CONTROL AXLE EXCHANGE

RBEM632V3023125-9 MAT'L 1018/1020 CR UNLESS OTHERWISE SPECIFIED TREAT
FINISH POWDER COAT YELLOW SURFACES = 125 SPEC FED #13538 1. BREAK ALL SHARP EDGES .015 x 45 'OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009 DRAWN BY: DUERFELDT CHECKED: MACKOVJAK OPPS APPR: ANDERSON QA APPR: USED ON MODEL LINDSAY APPROVED: GILBERT H175 SCALE 4:1 3/24/2016 SHEET 6 OF 6



FOOT